

Maxi Milk Filter

A Maxi milk filter is a vertical, top loading device with the capacity to filter milk from 520 cows. For herds exceeding 520 cows, two or more Maxi milk filters can be used in tandem and joined by specially fabricated manifolds. The strong, heavy duty enclosure of a Maxi milk filter ensures a complete seal and avoids distortion and leakage at this point.

A new hinged, swing-over top allows the retaining cap and saddle to be moved to one side parking the complete enclosure in a position that makes filter sleeve changing easier and more manageable.

A strong wire cage with three stainless steel spacers supports high quality Waikato Milking Systems filter sleeves that are retained by replaceable rubber filter sleeve retainers.

A choice of 50 or 63mm ferrule connections provide solid connection points for plumbing and are more than capable of containing the pumping pressures associated with modern high flow pump systems.

Maxi milk filters are manufactured to the highest standard and comply with current Fonterra regulations.

Specifications

Maximum no of cows per filter:	520
Overall Length including bottom port:	94.5mm
Weight:	16.5Kgs
Filter body diameter:	150mm
Single use filter sleeves size:	230x850mm
Filter density:	80 microns
Maxi Milk Filter – 50mm ports:	Pt no: 39800992
Maxi Milk Filter – 63mm ports:	Pt no: 39800801
Maxi Filter Sleeves:	Pt no: 39800957
Filter Sleeve Retainers (Rubber):	Pt no: 39800827

Note: 2 x 150mm Wall Clamps not included

Tested and Certified to meet the 2010 Fonterra standards for milk filters used in a NZ farm dairy.

